


PRODUCT INFORMATION



Application Type	Inground Lights
Colour Temperature	3500K, 6500k, 2700K, 3000K, 4000K, 6000K
Housing Type	Die Cast Aluminum, SS Ring
Dimmable	Yes
Controls	Analog, Dali, On/off
Wattage Upto	15W, 18W
Size	dia: 160mm, height: 170mm
Driver	Inbuilt, Remote



Physical Dimension(MM)

MODEL NO.	POWER	LIGHT SOURCE	LED COLOR	BEAM ANGLE	INPUT VOLT	CONTROL
ET-DIL1600615A	15-18W	6PCS CREE SMD	2200-6500K R/G/B/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/70°/80°/90°/100°/110°/120°/130°/140°/150°/160°/170°/180°	AC220-240V /AC110-240V	ON/OFF /Triac
ET-DIL1600615B	15W	6PCS CREE SMD	2200-6500K R/G/B/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/70°/80°/90°/100°/110°/120°/130°/140°/150°/160°/170°/180°	AC220-240V /AC110-130V	Triac/0-10V/DALI
ET-DIL1600618A	15-18W	6PCS CREE SMD	2200-6500K R/G/B/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/70°/80°/90°/100°/110°/120°/130°/140°/150°/160°/170°/180°	AC220-240V /AC110-130V	ON/OFF /0-10V/DALI/DMX512
ET-DIL1600618B	15-18W	6PCS CREE SMD	2200-6500K R/G/B/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/70°/80°/90°/100°/110°/120°/130°/140°/150°/160°/170°/180°	AC220-240V /AC110-130V	ON/OFF /0-10V/DALI/DMX512
ET-DIL1600618C	15-18W	6PCS CREE SMD	2200-6500K R/G/B/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/70°/80°/90°/100°/110°/120°/130°/140°/150°/160°/170°/180°	AC220-240V /AC110-130V	ON/OFF /0-10V/DALI/DMX512
ET-DIL1600618D	15-18W	6PCS CREE SMD	2200-6500K R/G/B/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/70°/80°/90°/100°/110°/120°/130°/140°/150°/160°/170°/180°	AC220-240V /AC110-130V	ON/OFF /0-10V/DALI/DMX512