


PRODUCT INFORMATION



Application Type	Inground Lights
Colour Temperature	3500K, 6500k, 2700K, 3000K, 4000K, 6000K
Housing Type	Die Cast Aluminum, SS Ring
Dimmable	Yes
Controls	Analog, Dali, On/off
Wattage Upto	18W, 24W, 30W
Size	dia: 182mm, height: 180mm
Driver	Inbuilt, Remote



MODEL NO.	POWER	LIGHT SOURCE	LED COLOR	BEAM ANGLE	INPUT VOLT	CONTROL
ET-DIL1820924	24W	9PCS CREE SMD	2200-6500K RGB/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/70°/22°/15°/55°/20°/60°	AC220-240V	ON/OFF /10-20-10V DALI
ET-DIL1820918	18W	9PCS CREE SMD	2200-6500K RGB/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/70°/22°/15°/55°/20°/60°	AC110-240V /AC110-120V	ON/OFF /10-20-10V DALI
ET-DIL1820930A	24-30W	9PCS CREE SMD	2200-6500K RGB/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/70°/22°/15°/55°/20°/60°	AC110-240V /AC110-120V	ON/OFF /10-20-10V DALI
ET-DIL1820930B	24-30W	9PCS CREE SMD	Turnable White 2700K/6500K	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/70°/22°/15°/55°/20°/60°	DC12V/DC24V /DC30V/DC48V	PWM DALI /DMX512
ET-DIL1820930C	24-30W	9PCS TYANSHINE SMD	RGB 3in1 RGBW 4in1	25°/40°/60°	DC12V/DC24V /DC30V/DC48V	PWM DALI /DMX512
ET-DIL1820930D	24-30W	9PCS TYANSHINE SMD	RGBW 4in1	25°/40°/60°	DC12V/DC24V /DC30V/DC48V	PWM DALI /DMX512